






Product Specification

Outdoor P6



Product Picture of Outdoor P6 Series



Hole Position of Outdoor P6 Series



Wiring Diagram of Data and Power



- Remark: 1. The recommended diagrams are for reference only.
 2. The recommended cabinet size is 960X960 mm.

Parameter of Outdoor P6 Series

	Parameter Name	Product Parameter
Module	LED Type	SMD2727
	Pixel Pitch	6mm
	Module Resolution (W×H)	32X32=1024 Pixels
	HUB	HUB75
	Module Dimension	192mm×192mm×18mm
	Module Weight	0.35±0.02kg
Optical	Single-dot Brightness Calibration	Support
	White Balance Brightness	4500 CD/m ²
	Standard Color Temperature	6500K (1000K ~ 9500K Adjustable)
	Beam Angle (Hor/Ver°)	140°/140°
	Contrast Ratio	3000 : 1
Electronic	Input Power <Max>	895W/m ²
	Input Power <Typical>	298W/m ²
	Power Supply Input Voltage	AC90 ~ 132V/ AC186 ~ 264V, Frequency 47-63 (Hz)
Performance	Frame Changing Frequency	60Hz
	Drive Mode	Constant Current Drive / 8 Scan
	Refresh Rate	1920Hz
	Processing Depth	12~14 Bit
	Video Support	2K HD, 4K UHD
Environment	Life Typical Value (HRS)	50000H
	Working Temperature/ Humidity Range (°C/RH)	-20°C~50°C / 10%-65%RH (No Condensation)
	Storage Temperature / Humidity Range (°C/RH)	-10°C~30°C / 10%-60%RH (No Condensation)

- Remark: 1. The above parameters are typical or recommended
 2. Product parameters or configuration adjustments without notice
 3. Customized products, please confirm the parameters with our company